



T-24 / T-22

BURNOSS SERVICE INFORMATION

Parts List for Routine Service of Kubota Industrial Diesel Engine Z482-E3

Also Refer to Engine Manufacturer's Service Manual for Engine Service Details
(Engine must be serviced first after 50, then every 200 hours of operation)

Description	Air Burners P/N	Manufacturer's P/N
Air Cleaner Element	3060-1022	Kubota 1G659-11222
Oil Filter	3060-1020	Kubota HH150-32430
Fuel Filter	3060-1021	Kubota 70000-43081
V-Belt (Engine)	3060-1023	Kubota 15881-97010
Electrical System Fuse 40A	5000-0302	NAPA BK7821079
CAT Battery	5000-2050	CAT 8C-3612

Tire Pressure	80 psi
Tire Size	LT 215 85 R16
Engine Oil	15W40 Diesel Grade
Engine Coolant	Low Silicon Anti-Freeze (Green). Units are shipped from factory with 50-50 mixture green antifreeze/water.
Hydraulic Oil	ISO32 Synthetic Hydraulic oil, factory installed is Amsoil HVH05-EA. (cold weather option is ISO22 synthetic, i.e. Amsoil HVG05EA). Capacity is approximately 2.16 gallons (8.19 liters).
Fuel Tank Capacity	Minimum 9.9 Gallons (8.2 Liters)
Consult Operating Manual for PTO and engine-to-fan coupler service and adjustment.	

AIR BURNERS, INC.

4390 SW Cargo Way • Palm City, FL 34990
Phone 772-220-7303 • FAX 772-220-7302
E-mail: info@airburners.com • www.AirBurners.com
© 2017 Air Burners, Inc.