

**SERVICE INFORMATION**
**Kubota or Perkins Engines**
**Parts List for Routine Service of  
Kubota Industrial Diesel Engine V2403-TE**

**Also Refer to Engine Manufacturer's Service Manual for Engine Service Details**  
(Engine must be serviced first after 50, then every 200 hours of operation)

Description	Air Burners P/N	Manufacturer's P/N
Air Filter (Primary)	5000-1334	Donaldson P827653
Air Filter (Safety)	5000-1229	Donaldson P829332
Oil Filter	5000-1327	Kubota 70000-74035
Fuel Filter	5000-1299	Kubota 16631-43560
Fuel/Water Separator Filter	5000-1297	Racor R20P
V-Belt (Engine)	5000-1341	Kubota KUBIG521-97010
V-Belt Air fan (2 Belts)	5000-0008	Optibelt Redpower II 5V1400
Electrical System Fuse 40A Amp ID: Green, Style: MAXI	5000-0302	NAPA BK7821079
CAT Battery	5000-2050	CAT 8C-3612

Tire Pressure	80 psi
Engine Oil	15W40 Diesel Grade
Engine Coolant	Low Silicon Anti-Freeze (Green). Units are shipped from factory with 50-50 mixture green antifreeze/water.
Bearing Lubricant	NLGI Grade 2
Fuel Tank Capacity	Minimum 46 Gallons (174 Liters)
Consult Operating Manual for PTO and engine-to-fan coupler service and adjustment.	

**AIR BURNERS, INC.**

4390 SW Cargo Way • Palm City, FL 34990  
 Phone 772-220-7303 • FAX 772-220-7302  
 E-mail: [info@airburners.com](mailto:info@airburners.com) • [www.AirBurners.com](http://www.AirBurners.com)  
 © 2017 Air Burners, Inc.

## **SERVICE INFORMATION**

### **Parts List for Routine Service of**

### **Perkins Industrial Diesel Engine 404T.22T**

**Also Refer to Engine Manufacturer's Service Manual for Engine Service Details**

(Engine must be serviced first after 50, then every 200 hours of operation)

Description	Air Burners P/N	Manufacturer's P/N
Air Filter (Primary)	5000-2054	Donaldson P827653
Air Filter (Safety)	5000-2055	Donaldson P829332
Oil Filter	5000-1323B	Perkins 140517050
Fuel Filter	5000-1303A	Perkins 26561117
V-Belt (Engine)	5000-1340	Perkins T80109107
V-Belt Air fan (2 Belts)	5000-0008	Optibelt Redpower II 5V1400
CAT Battery (12V, CCA 800, AH 50)	5000-2050	CAT 8C-3612

Tire Pressure	80 psi
Engine Oil	15W40 Diesel Grade
Engine Coolant	Low Silicon Anti-Freeze (Green). Units are shipped from factory with 50-50 mixture green antifreeze/water.
Bearing Lubricant	NLGI Grade 2
Fuel Tank Capacity	Minimum 46 Gallons (174 Liters)
Consult Operating Manual for PTO and engine-to-fan coupler service and adjustment.	

#### **AIR BURNERS, INC.**

4390 SW Cargo Way • Palm City, FL 34990

Phone 772-220-7303 • FAX 772-220-7302

E-mail: [info@airburners.com](mailto:info@airburners.com) • [www.AirBurners.com](http://www.AirBurners.com)

© 2017 Air Burners, Inc.