

**T24**
BURNBOSS

SERVICE INFORMATION

Parts List for Routine Service of Kubota Industrial Diesel Engine Z482-E4

Also Refer to Engine Manufacturer's Service Manual for Engine Service Details
(Engine should be serviced after first 50 hours then every 200 hours of operation or as needed)

Description	Air Burners P/N	Manufacturer's P/N	Service Interval
Air Cleaner Element	3060-1022	Kubota 1G659-11222	1 Year or as needed
Oil Filter	3060-1020	Kubota HH150-32430	200 Hours
Fuel Water Separator Element	5000-2462	Kubota 1T021-43560	200 Hours or as needed
In-line Fuel Filter	5000-2463	Kubota 12581-43012	200 Hours or as needed
V-Belt (Engine)	3060-1023	Kubota 15881-97010	200 Hours or as needed
Electrical System Fuse 40A Automotive ATC Blade Fuse	5000-1987	NAPA BK7822022	As needed
Battery, 12V, Max 120 Ah; Max. CCA 800; Min. CCA 750; RC 130	5000-2472	Interstate Batteries 24M-XHD	2 Years or as needed

Tire Pressure	105 psi (724 kPa) Cold
Tire Size	ST235/80R16
Rim	16 x 6 (8 Lugs)
Engine Oil	15W40 Diesel Grade
Engine Oil Capacity	2.6 qt. (2.5 L)
Bearing Lubricant	NLGI Grade 2 (Axle System and Wheel Bearings)
Engine Coolant	Low Silicon Anti-Freeze (Green). Units are shipped from factory with 50-50 mixture green antifreeze/water.
Hydraulic Oil	ISO32 Synthetic Hydraulic oil, factory installed is Amsoil HVH05-EA. (cold weather option is ISO22 synthetic, i.e. Amsoil HVG05EA). Change Hydraulic Oil every 1 to 2 years, depending on condition and environment.
Hydraulic Oil Capacity	Approx. 2.16 gal. (8.19 L).
Break-Away Switch	12V Battery - See Owner's Manual
Fuel Tank Capacity	Minimum 10 gal. (37.8 L)

AIR BURNERS, INC.

4390 SW Cargo Way • Palm City, FL 34990

Phone 772-220-7303

E-mail: support@airburners.com • www.AirBurners.com

© 2025 Air Burners, Inc.

Rev. 07.14.2025