

## SERVICE INFORMATION

### Parts List for Routine Service of Kubota Industrial Diesel Engine Z482-E4

Also Refer to Engine Manufacturer's Service Manual for Engine Service Details

(Engine must be serviced first after 50, then every 100 hours of operation)

Description	Air Burners P/N	Manufacturer's P/N	Service Interval
Air Cleaner Element	3060-1022	Kubota 1G659-11222	1 Year or as needed
Oil Filter	3060-1020	Kubota HH150-32430	200 Hours
Fuel Water Separator Element	5000-2462	Kubota 1T021-43560	200 Hours or as needed
In-line Fuel Filter	5000-2463	Kubota 12581-43012	200 Hours or as needed
V-Belt (Engine)	3060-1023	Kubota 15881-97010	200 Hours or as needed
Electrical System Fuse 40A Amp ID: Green, Style: MAXI	5000-0302	NAPA BK7821079	As needed
Battery, 12V, Max 120 Ah; Max. CCA 800; Min. CCA 750; RC 130	5000-2472	Interstate Batteries 24M-XHD	2 Years or as needed
Tire Pressure	105 psi (724 kpa) Cold		
Tire Size	ST235/80R16		
Rim	16 x 6 (8 Lugs)		
Engine Oil	15W40 Diesel Grade		
Engine Coolant	Low Silicon Anti-Freeze (Green). Units are shipped from factory with 50-50 mixture green antifreeze/water.		
Hydraulic Oil	ISO32 Synthetic Hydraulic oil, factory installed is Amsoil HVH05-EA. (cold weather option is ISO22 synthetic, i.e. Amsoil HVG05EA). Capacity is approximately 2.16 gallons (8.19 liters). Change Hydraulic Oil every 1 to 2 years, depending on environment.		
Break-Away Switch	12V Battery - See owner's manual		
Fuel Tank Capacity	Minimum 10 Gallons (37.8 Liters)		

#### AIR BURNERS, INC.

4390 SW Cargo Way • Palm City, FL 34990

Phone 772-220-7303

E-mail: support@airburners.com • www.AirBurners.com

© 2022 Air Burners, Inc.

Rev. 11.11.2022